

SPM – 450 P-AU


Collar Type For Non-Free Flowing Products




Global Standards. Unmatched Performance

SPECIFICATIONS

Sealing Style	Centre Seal
Speed	30-40 Strokes / minutes max. (Depends upon the type of product & quantity to be filled)
Packing Material	Laminate with heat sealable layer on one side
Product To Be Packed	Non-free flowing Powder/ Spices etc.
Servo Make	Omron/Delta 2 Kw
Plc	Delta/Omron
Power Consumption	4 – 5 KW
Max Roll Width	450 mm
Max Roll Dia	350 mm
Reel Core Dia	76 mm
Main Motor	2.2 KW , 3 Phase, 415 Volts
Dimension of Machine	Length 2000 mm Width 1500 mm Height 3000 mm
Net Weight	1500 Kg.
Gross Weight	2000 Kg.
Air Compressor	3 HP ,6Kg / cm sq
Temperature Controller	PID based
Machine Colour	Shell Grey / Powder Coated
Vertical & Horizontal Sealing	Mechanically Cam Driven
Batch Cutter Operation	Pneumatic
Film – Draw Off	Clutch brake
Film Tracking	Manual
Filling	Fully controlled by Servo
Display Setting	Through Touch panel screen
Safety	Machine Covered by Acrylic Sheet
Machine Structure	All Contact Parts SS 316



CENTER SEALED



CENTER SEALED WITH SIDE GUSSET

Shubham Flexible Packaging Machines Pvt. Ltd
 B-8A, Sector 59 Part II, Ballabgarh, Faridabad - 121004, Haryana (India)
 Phone: +91 129 4296100, 4296123, +91 129 4272350-55
 Fax: +91 129 4272351

eMail: ccare@shubhampack.com, marketing@shubhampack.com,
export@shubhampack.com

www.shubhampack.com