

SPM – 600 L


For Liquids and Pastes




Global Standards. Unmatched Performance

SPECIFICATIONS

Sealing Style	4 Side Seal
Speed	60 Strokes / minutes maximum (Depends upon the type of product & quantity to be filled)
No. of Tracks	Depends upon the width of the pouch
Laminate Specification	Width - 600 mm max. Roll Dia - 450mm.max. Reel Core I.D. - 150/76 mm
Max. Length of Pouch	200mm
Packing Material	Laminates with one side heat sealable
Filling Capacity	1ml-300ml
Product To Be Packed	Liquids / Pastes within dosable viscosity range
Sealing Drives	Mechanical – Cam driven with individual sealing jaw setting.
Filling Mechanism	Piston Filler / Solenoid Valve
Sealing Type	As per customer requirement
Perforation and Cutting	As per customer requirement
Laminate Roll Unwind	Manual
Laminate Draw Off System	Through Clutch/Brake
Control Panel	Air Cooled with all applicable standards
Contact Parts	SS 316
Batch Cutter Operation	Pneumatic
Mat Format	As per Requirement
Electrical Spec.	Main Motor – 2.2 KW, 3 Phase, 415 V
Layout Dimensions	Length 3200 mm Width 2600 mm Height 2100 mm
Machine Weight	Net Weight 1500 kgs. Gross weight 1800 kgs.
Air Compressor	3HP, Pressure 6kg/cm sq.
Power Consumption	6KW Approx.
Scrap Rate	Less than 2%*
Machine Color	Shell Grey – Powder coated.
Weight Variation	Within +/- 1%** of the filled quantity
Temp Controller	PID Based
Embossing Provision	Provision Given (Digits not included)



4 SIDE SEALED IN MAT FORMAT



4 SIDE SEALED

* depending on laminate quality, product consistency and operator's efficiency
** depending on product consistency

Shubham Flexible Packaging Machines Pvt. Ltd
B-8A, Sector 59 Part II, Ballabgarh, Faridabad - 121004, Haryana (India)
Phone: +91 129 4296100, 4296123, +91 129 4272350-55
Fax: +91 129 4272351

eMail: ccare@shubhampack.com, marketing@shubhampack.com,
export@shubhampack.com

www.shubhampack.com